

PROJECT NAME:	DATE:	TYPE:
SPECIFIER:	PREPARED BY:	
PART NO.:		



LED POWER SUPPLIES

TBD.PSHK

NON-DIMMING DRIVER



TBD.PSHK-30W-24V
6.5 in. x 3.63 in. x 1.03 in.

TBD.PSHK-60W-24V
7.4 in. x 3.63 in. x 1.03 in.

TBD.PSHK-96W-24V
8.67 in. x 3.67 in. x 1.62 in.

TBD.PSHK SERIES includes 30W, 60W, 96W, Class 2, non-dimming drivers. Includes integrated UL listed aluminum junction box. Suitable for indoor or outdoor use, the housings are IP66 rated.

FEATURES

- Output: 24V DC
- Output: 30W, 60W, 96W
- Short Circuit and Overload-Protected Output
- Shut down, Re-power on
- Operating voltage: 100 ~ 277V AC
- Residential or Commercial Applications
- Factory De-rated
- 10% Minimum Load
- Class 2

Dimensions:

30W 6.5" x 3.63" x 1.02"

60W 7.4" x 3.63" x 1.02"

96W 8.67" x 3.67" x 1.62"



ORDERING GUIDE

TBD.PSHK

WATTAGE

30W - 30 Watt

60W - 60 Watt

96W - 96 Watt

VOLTAGE

24V - 24 Volt



TBD LED SOLUTIONS

218 E Valley Rd, Ste 104 – PMB377, Carbondale, CO 81623
www.tbledsolutions.com

REV 02222021