

PROJECT NAME:	DATE:	TYPE:
SPECIFIER:	PREPARED BY:	
PART NO.:		



# LED POWER SUPPLIES

## TBD.PS

### PLUG-IN CONSTANT VOLTAGE DC DRIVER



TBD.PS plug-in drivers are commonly used for DC LED systems where quick and easy installation are desired. These plug-in drivers are available in a range of wattages and are offered in 12V and 24V DC output.

**NOTE:** To maximize performance, do not load the power supply to more than 80% of its labeled rating. All power supplies listed above are UL listed with constant voltage output of 12V or 24V DC.



## ORDERING INFO AND SPECS

### 12V DC Plug-In Drivers

ITEM #	WATTAGE	INPUT	WET/DRY	DIMENSIONS
TBD.PS-15W-12V	15W	120V AC	Dry Location	2.9 in. x 1.7 in. x 1.1 in.
TBD.PS-24W-12V	24W	120V AC	Dry Location	3.8 in. x 1.7 in. x 1.4 in.
TBD.PS-45W-12V	45W	120V AC	Dry Location	3.8 in. x 1.7 in. x 1.4 in.
TBD.PS-65W-12V	65W	120V AC	Dry Location	4.6 in. x 1.2 in. x 1.2 in.

### 24V DC Plug-In Drivers

ITEM #	WATTAGE	INPUT	WET/DRY	DIMENSIONS
TBD.PS-15W-24V	15W	120V AC	Dry Location	2.9 in. x 1.7 in. x 1.1 in.
TBD.PS-24W-24V	24W	120V AC	Dry Location	3.8 in. x 1.7 in. x 1.4 in.
TBD.PS-45W-24V	45W	120V AC	Dry Location	3.8 in. x 1.7 in. x 1.4 in.
TBD.PS-65W-24V	65W	120V AC	Dry Location	4.6 in. x 1.2 in. x 1.2 in.